

UCT13-5

Dodge/Chrysler/Jeep uConnect Interface for 5" monitor NTV-KIT438







BHM 11/03/13 NTV-DOC123

Overview

The Dodge uConnect Camera Interface (UCT13-5) system integrates an aftermarket rear camera into the factory uConnect 5" touch screen monitors in select Dodge, Ram and Jeep Grand Cherokee vehicles.



Wire Side

*If your camera draws more than 1 amp, use this wire trigger a relay for camera power.

Agreement: End user agrees to use this product in compliance with all State and Federal laws. NAV-TV Corp. would not be held liable for misuse of its product. If you do not agree, please discontinue use immediately and return product to place of purchase. This product is intended for off-road use and passenger entertainment only.

UCT13-5 Module Installation

- 1. Remove the factory radio. Gather the *Plug & Play T-harness* and connect the female side to the factory 44-pin plug. Make certain the lock connects together securely.
- After installing a rear camera (power cam with ACC), connect the signal RCA to the *yellow RCA* on the *male side* (side going into monitor) of the *Plug & Play T-harness*. The other side of the *yellow RCA* can be left disconnected.
- 3. Connect the UCT-13 module to the 18-pin connector found in the Plug & Play T-harness.
- 4. Connect the monitor to the male side of the Plug & Play harness. Reconnect all other plugs to the monitor.
- 5. Close all doors (including trunk, if applicable) and lock the car. Wait 5-10 minutes for the CAN-bus to fully go to sleep.
- 6. Enter vehicle, turn ignition to 'ON' and place the vehicle in reverse (programming and reverse activation are automatic) to test for proper operation.
- 7. Replace dash pieces as necessary.

Installation Diagram

