

Parrot Updater

Updating the internal Bluetooth firmware for the Nav-TV Tooki

Before starting: Pairing the computer to the Tooki

If the Tooki update was performed immediately prior to the Parrot update, then no additional steps are necessary. If only the Parrot update is being performed, then the computer must first be paired to the Tooki. This is done via the computer's Bluetooth manager software; select the option to add a new Bluetooth device, search for the Tooki, and select the option to choose a PIN code or use a provided PIN code. The PIN code for the Tooki is **6888**.

To update the embedded Parrot chip in the Tooki

1. After unzipping the "Parrot Updater.zip" file to a desired folder, locate the "Parrot Updater.exe" file in that folder and run it.
2. Follow the instructions in the Wizard by choosing Next → (choose a different directory, if necessary) → Next → Install → Finish.
3. Start → Programs → Parrot Software Update Tool → Parrot Flash Update Wizard.
4. Follow the instructions in the Wizard by choosing Next → Next → Browse (navigate to the folder that the Parrot Updater file was unzipped to,) select the appropriate "CK505X_(version).plf" file → Next → select "Bluetooth connection" → Next → Search Devices (make sure the Tooki and vehicle are on,) you may need to Search several times, select your Tooki.
5. **IMPORTANT: Dial 2*220022* and press the Dial/Pickup button on your radio. The screen should change to "Update PIN:6888" and a call timer will start. Make sure the call timer starts before proceeding to step 6!**
6. On the computer, click Next → observe the progress of the Update on both the radio (which should now say "Downloading") and the PC.
Note that when loading Parrot version 3.12, the updater will pop up a box saying that the new software is older than the one in the unit; this is normal, so agree to continue.
7. The call on the radio should go from Downloading → Flashing → resetting to the main screen. If the update "call" lasts longer than 10 minutes in "Flashing" then manually end the call on the radio.
NOTE: DO NOT click "Finished" on the Parrot Updater or close the Updater until the message on the radio screen changes to "Flashing"!
8. Once the update is complete and the Tooki has been fully reset by turning off the vehicle and removing the key for 1-2 minutes, access the TEL screen of the radio and dial "5*110011*4" then verify that the 3 digits at the end of the second line displayed correspond to the version that was selected.

After updating the Parrot chip

All pairing information in the Tooki will be erased, including the information it normally exchanges with the phone to properly connect. Therefore, you **MUST** delete the Tooki from the device list of all phones that were paired to it previously and re-pair those phones. This also means that you must delete the Tooki from the Bluetooth device manager of the computer that was used to update it.